ACCESSORIES



Close-Focus Tip

The Close-Focus Tip allows the user to view defects, such as tiny cracks, up close with high magnification. The tip threads directly onto the Hawkeye V2 Video Borescope. Double threads are utilized to prevent the tips from falling off.



90° Prism Tip

The 90° Prism Tip threads directly onto the Hawkeye V2 Video Borescope, allowing the user to view the walls of pipes and tubes and to more easily inspect certain turbine blades or engine valves in difficult engines. Double threads are utilized to prevent the tips from falling off.



V2 Rigidizer

When you push a flexible scope through a hole into a large open cavity it is difficult to direct and orient the scope tip. The V2 Rigidizer tube allows the user to easily direct the scope to whatever you want to see. Available for 4 mm and 6 mm scopes.

Length: 17" **Outside Diameters:** 4 mm, 0.188" (4.8 mm) 6 mm, 0.313" (8 mm)



V2 Stand

When you're working on a benchtop location, in a repair station, factory, or foundry, the V2 Stand allows you to set the scope on the benchtop for hands free operation.



Hawkeye® V2 Video Borescopes

Outside Diam.	Length	Articulation	Sheath	Model #
4 mm	1.5 m (4'11")	2-way	Tungsten	V2 040 1500 2
4 mm	1.5 m (4'11")	4-way	Tungsten	V2 040 1500 4
4 mm	3.0 m (9′10″)	4-way	Tungsten	V2 040 3000 4
6 mm	1.5 m (4'11")	4-way	Tungsten	V2 060 1500 4
6 mm	3.0 m (9′10″)	4-way	Tungsten	V2 060 3000 4
6 mm	6.0 m (19'8")	4-way	Tungsten	V2 060 6000 4



Hawkeye V2 Video Borescope Accessories

Item	Model #		
4 mm Close-Focus Tip	V2-TIP-4CF		
6 mm Close-Focus Tip	V2-TIP-6CF		
4 mm 90° Prism Tip	V2-PTIP-4-90		
6 mm 90° Prism Tip	V2-PTIP-6-90		
V2 Rigidizer 4 mm	V2-RT4		
V2 Rigidizer 6 mm	V2-RT6		
V2 Stand	V2-Stand		
V2 Charger	V2 Charger		
Spare Battery	PVM50 BATTERY		
Spare Battery Charger	PVM50 Charger		
V2 LED Light Source	V2-LED KIT		
Light Source Batteries	V2-LED BAT		
Light Source Battery Charger	V2-LED CHARGER		
Spare Battery Charger V2 LED Light Source Light Source Batteries	PVM50 Charger V2-LED KIT V2-LED BAT		

f 8