## E-Series Video Borescopes

The E-Series Video Borescope features diameters of 2.0 and 2.8mm. The new small diameters allow our customers to transition from fiber-based solutions to modern-day video technology. The E-Series Video Borescopes offer 4-way joystick articulation, image and video capture, and 4-hour battery life combined with a compact and durable design. The Hawkeye E-Series design allows end-users to easily remove and replace the insertion tube, eliminating repair downtime.



E-Series Video Borescopes Specifications				
Diameter	2.0mm and 2.8mm (.078 and .110") (+/- 0.2mm)			
Length	1, 2 and 3 meters			
Articulation	150° (+/- 10°)			
Field-of-View	100° Diagonal (+/- 10°)			
Depth-of-Field	3-50mm			
Direction of View	0°			
Sheath	Tungsten Braid			
Camera	400x400			
Display	3.5" HD Display			
Illumination	Integrated White LED (Tip LED 2.0mm)			
Interfaces	HDMI, USB, SD Card			
Battery	4hr, 3.7V, 3200 mAh			
Recording Media	JPEG/BMP, MPEG4			
Operating Temp	Probe: - 20 to +60C (-4 to +140 F): Display Unit: -10to +50C (14 to +122F)			
Storage Temp	- 20 to + 60 C (-4 to +140 F)			
Weight	1.5lb			
Environmental	Sheath: IP67			

E-Series Video Borescopes Price List					
Diameter	Length	Articulation	Sheath	Model #	
2.0mm (.078")	1 meter (3' 3")	4-Way Joystick	Tungsten	ES 020 1000 4	
2.0mm (.078")	2 meter (6' 6")	4-Way Joystick	Tungsten	ES 020 2000 4	
2.0mm (.078")	3 meter (9' 9")	4-Way Joystick	Tungsten	ES 020 3000 4	
2.0mm (.078")	4.5 meter (14' 9")	Non-Articulating	Tungsten	ES 020 4500 NA	
2.8mm (.110")	1 meter (3' 3")	4-Way Joystick	Tungsten	ES 028 1000 4	
2.8mm (.110")	2 meter (6' 6")	4-Way Joystick	Tungsten	ES 028 2000 4	
*Kits Include: Video Borescope, SD Card, SD/USB Adapter, Charging Cables and Rugged Carrying Case.					





